Pioneering for You



Productbrochure

Wilo-Actun OPTI HS Submersible pump



Smart solutions for renewable energies.

Wilo is a premium supplier for building services, water management and industrial applications. We make complex technologies user-friendly, simple to operate, energyefficient and powerful for our customers. In the end, the main focus of everything we do is people. We offer them outstanding products, system solutions and services. Founded in Dortmund in 1872 as a factory for copper and brass goods, Wilo has evolved from being a local specialist to a global player in the course of its long and successful history. We are well-acquainted with questions that will shape our future and we develop technologies that provide answers. Global megatrends are having a profound and lasting impact on our lives. As we address these trends, we concentrate on globalisation, urbanisation, climate change, energy scarcity, water shortage as well as technological advances and digitalisation – important issues for your day-to-day work. Which makes them important to us, too. Competition for raw materials and resources is intensifying. Energy shortage and water shortages are two major consequences. In

addition, outdated power infrastructures, growing water pollution and highly inefficient usage patterns aggravate the situation. That is why Wilo focuses on developing both flexible, high-efficiency solutions that adapt to their environment and highly efficient technologies that conserve resources.

Our innovative products let you satisfy requirements for high system efficiency and the sustainable use of precious resources. Ultimately, the efficient use of energy and water is becoming more and more important everywhere you look.

The Wilo-Actun OPTI HS pumps, powered by renewable energy sources, is a new range with built-in inverter.

The pumps may be powered by AC or DC with a wide range of operating voltage (90 – 265 VAC/90 – 400 VDC). This means that the pumps can be connected to solar panels, batteries, wind turbine and diesel generator. A special software algorithm allows for adjusting the hydraulic performance to each source and to the available power while maximizing the pumped water.



All the advantages of built-in electronics

The built-in electronics inside the motor avoids the use of shielded cables and output filters and it is the ideal solution for any application in remote locations without surveillance and climatically adverse.

In fact, in the traditional solutions, the solar inverter is placed above ground and, being exposed to the weather, could suffer of:

- → Overheating
- → Water infiltration
- → Thermal shock
- \rightarrow Damaging by animals or people

Wilo-Actun OPTI HS pumps do not need of any external electronic component; it is just enough to connect the pump cable to the power source and start to extract water. The built-in electronic is directly cooled by the water flow; the operating temperature of the electronic components is so low as to ensure considerably longer a life than a on-surface inverter affected by high temperature, humidity, dust and solar radiation.



Maximum Power Point Tracking



Optional External Control Module

In the application with solar panel, the function MPPT (Maximum Power Point Tracking) maximizes the input power for various conditions of radiation and temperature.

When radiation grows, pump increases the rotation speed as well as the water flow .

When radiation decreases (presence of clouds or different hours of the day), pumps reduces the speed and thus the water flow but still provide water until the radiation falls below the minimum value to ensure the operation.

Installation

Wilo-Actun OPTI HS pump can be installed with External control module or without it, so becoming a "plug and pump" system. If no external control module is used, signal cables can be used to control pump ON/OFF the connecting, for example, a float switch. All the protections against overload, overvoltage and dry running are integrated into the on board inverter.

If the signal cables are connected to the External control module, it is possible to:

- → Control the electric parameters (current, power, voltage).
- → Record and store all the alarms related to the working hours.
- → Connect a pressure or a flow sensor to control the pump performances.
- → Connect a pressure or float switch.
- → Provide an alarm digital output for remote control.



Raw water intake Single pumps

5

Use of auxiliary genset

If solar energy is absent or not enough, it is possible to feed the pump with an auxiliary genset to grant the desidered pump performances.

An AC/DC selector is used to change the power source.



Integrated on board protection

Protections against overvoltage, overload and dry running are integrated into the pump electronic circuit.

Electronic protection against dry running avoids the use of the probes.



Raw water intake6 Single pumps

Wilo-Actun OPTI HS



Centrifugal pump

- \rightarrow Impellers and diffusers in stainless steel.
- → Built-in no return valve.



Motor

- \rightarrow AC permanet magnet motor
- → Resined and incapsulated stator made of stainless steel AISI 304.
- \rightarrow Water cooled rotor.
- \rightarrow Kingsbury thrust bearing.



Built-in inverter module (MINT) → Completely filled of resin.





Customer benefits

- \rightarrow entirely made of stainless steel AISI 304 to grant a long life of the components.
- → Pump, motor and hydraulic components can be easily disassembled to have simple maintenance and replacement operations.
- \rightarrow Impellers and diffusers in stainless steel and built–in no return valve
- \rightarrow AC–Permanent magnet motor
- \rightarrow Resined and incapsulated stator made of stainless steel AISI 304.
- → Removable power cable.



The helical rotor pump

The Wilo–Actun OPTI HS is equipped with a helical rotor that moves within a double helix rubber stator. The rotor is made of AISI 316 stainless steel and coated with a hard chrome surface.

During operation, the rotor moves on the rubber surface and it's lubricated by the pumped water.

The flow rate is directly proportional to pump speed while the pressure supplied is kept almost constant.

In this way, unlike a centrifugal pump, the helical rotor pump provides high head even at low rpm, ensuring water on surface even with very low available power or low irradiation. In addition, the helical rotor pumps feature higher hydraulic efficiency than centrifugal pumps of same flow. This saves in the number of PV panels necessary for the application.

Permanent magnets motor

The Wilo-Actun OPTI HS is equipped with AC permanent magnets motor. The rotor uses Neodymium magnets coated with thin layers of Copper and Nickel, to ensure, in addition to superior magnetic performance, greater reliability and durability.

High motor efficiency and high starting torque make pump moving even in low light conditions.

The integrated inverter module realizes the conversion from DC energy into useful electrical energy to drive the engine efficiently and, at the same time, adjusts the pump speed in relation to available irradiation, maximizing the power extracted (MPPT).

Over-current, over-temperature, lack of water protections are integrated on-board.

Pump selection in a PV system

For the correct selection of a pump to be used in a photovoltaic (PV) system, it is necessary to know:

- → Desired daily water quantity
- → Total head (static + dynamic)
- → Installation location
- → Working period (seasonal or year)
- \rightarrow Average daily radiation per year, minimum and maximum (KWh/m²)
- → Average daily radiation per months, minimum and maximum
- → Optimal tilt angle of the photovoltaic panels

Starting from daily radiation could be considered the number of hours with 1kW/m², standard value to which PV panels performances are referred. Dividing the required water quantity by the hours, nominal pump is calculated and, in addition to the required head, the right pump could be selected.



Sizing example

Daily delivery $Qd = 27 m^3$ Total head H = 50 m

Location : Casablanca, Marocco Latitude: 33° 35' Longitude: 7° 37' Optimal tilt angle is 34°.

If the pump shall deliver the required 27 m³ each day of the full year, consider the lowest monthly radiation of a year that is 4.07 kWh/m² (4.07 h @ 1kW/m2). Considering the required daily delivery Qd, a pump granting 27/4.07 = 6.63 m^3 /h should be selected.

If the pump is used only in the summer (June, July, August), consider the average daily radiation for the selected months. That is $6,68 \text{ kWh/m}^2$ ($6,68 \text{ h} @ 1 \text{kW/m}^2$).

	Year	Summer		
Q [m³/h]	6.63	4,04		
H [m]	50	50		
OPTI HS	08/05	05/08		
P1 [W]	3500	2000		
PV panels	14	8		
Series	7	8		
Parallel	2	1		

Sizing considering photovoltaic panels of 250 Wmpp, nominal voltage 30.4 Vmpp, nominal current 8.3 Impp, no load voltage 37.3 Voc.

Pump curves Wilo-Actun OPTI HSH 4.02-02



External control module (CM) installation is recommended o	n dashed lines operation
-----------------------------	---------------------------------	--------------------------

Technic	al data									
HSH	Voltage	Max. absorbed current	Power factor	Max. absorbed power	Dimen- sion	Deliv- ery	Pump weight	Max. diame- ter*	Packing size	total weight
		l _{max}		P ₁				Ø		
		A		W	mm		kg	mm	cm	kg
4.02-02	90 – 400 VDC 90 – 265 VAC	13 (100 VDC) 13 (100 VAC	1	1300	1350	1¼	19,5	101	120x20x29	20,5

*Max. external diameter invluding cable and cable cover

Raw water intake10Single pumps

Pump curves Wilo-Actun OPTI HSI 4.05-04, HSI 4.05-04



External control module (CM) installation is recommended on dashed lines operation

Technica	al data									
HSI	Voltage	Max. absorbed current	Power factor	Max. absorbed power	Dimen- sion	Deliv- ery	Pump weight	Max. diame- ter*	Packing size	total weight
		l max		P ₁		. <u>.</u>		Ø		
		А		W	mm		kg	mm	cm	kg
4.05-04	90 – 400 VDC 90 – 265 VAC	16 (100 VDC) 16 (100 VAC)	1	1600	879	1½	19,5	101	120x20x29	20,5
4.05-08	90 – 400 VDC 90 – 265 VAC	16 (187 VDC) 16 (187 VAC)	1	3000	1013	1½	22	101	120x20x29	23

*Max. external diameter invluding cable and cable cover

Raw water intake Single pumps 11

Pump curves Wilo-Actun OPTI HSI 4.08-03, HSI 4.08-05



External control module (CM) installation is recommended on dashed lines operation

Technica	l data									
HSI	Voltage	Max. absorbed current	Power factor	Max. absorbed power	Dimen- sion	Deliv- ery	Pump weight	Max. diame– ter*	Packing size	total weight
		I _{max}		P _i				Ø		
		А		W	mm		kg	mm	cm	kg
4.08-03	90 – 400 VDC 90 – 265 VAC	16 (113 VDC) 16 (113 VAC)	1	1800	858	1½ 2	19,4	101	120x20x29	20
4.08-05	90 – 400 VDC 90 – 265 VAC	16 (187 VDC) 16 (187 VAC)	1	3000	950	1½ 2	21	101	120x20x29	22

*Max. external diameter invluding cable and cable cover

Raw water intake

12 Single pumps

Materials





Pos.	Description	Material
1	Power supply removable connec- tor with cable for drinking water applications	AISI 304 + ACS-KTM-WRAS compliant
3	MINT: Electronic Integrated Module	
4	Cable guard	AISI 304
5	Lower thrust bearing	AISI 304
6	Rubber diaphragm	EPDM
7	Lower carbon bush	CTI25
8	Tilting disc	AISI 304
9	Pads	AISI420j
10	Carbon disc	CTI25
11	Shaft with rotor	AISI 431
12	Canned type stator	AISI 304
13	Upper carbon bush	CTI25
14	Upper thrust bearing	Teflon
15	Ceramized sleeve	AISI 304 + Ceramic
16	Lip seal	FKM
17	Rotating sandguard	NBR
18	Pump filter	AISI 304
19	Pump bracket	AISI 304
Centri	^f ugal mpump	
20	Diffusers	AISI 304
21	Impellers	AISI 304
22	Pump shaft	AISI 304
23	Discharge	AISI 304
24	Straps	AISI 304
Helicoi	dal rotor pump	
25	No-return valve	AISI 304
26	Helicoidal stator	EPDM + AISI 304
27	Supporting pipe	AISI 304
28	Junction	AISI 304
29	Helicoidal rotor	AISI 316 cromed
30	Safety hook	AISI 304
31	Flexible shaft	AISI 316
32	Pump adaptor	AISI 304

General characteristics

Wilo-Actun OPTI HS	
Max. temperature of the liquid	35 °C (92 °F)
Min. cooling speed of the liquid	0.2 m/s
Characteristics of the pumped liquid	clean, chemically not aggressive, not explosive, without solids and fibres con- tent, with max. 50 g/m3 sand content
Protection grade	IP68
Max. immersion depth	150 m
Materials	Motor and pump in AISI 304 stainless steel
Cable	Flat cable ACS – WRAS – KTM approved
Control Module (external)	
Max. ambient temperature	50 °C (122 °F)
Protection grade	IP55
Materials	Aluminium enclosure, PVC labels , cable gland in polyam–ide (PA), display mem– brane in polyester (PE)
Analog input	2 input 4–20 mA + 2 input 4–20 mA or 0–10 V settable by the user
Digital input	4 input N.A o N.C settable by the user
Digital output	2 relays output 5 A , 250 VAC, N.A. o N.C settable by the user
User display	display LCD backlit, 16 characters x 2 rows, 5 buttons

Shortcircuit protection

by fuse

A Wilo-Actun OPTI HS pump can be installed both vertically and horizontally with the outlet never be lower the horizontal axis.

To ensure a proper cooling if Wilo-Actun OPTI HS is not installed in a well, it is necessary to use a cooling sleeve to grant the minimum cooling speed of the liquid.







wilo

www.wilo.com



Technische Änderungen vorbehalten. Weitere Kontaktdaten unter www.wilo.com

Pioneering for You